Tender text

PA-4120

PA power amplifer

• 4 x 120 W
• Routing switches for parallel operation on 2 channels each
• Temperature-controlled fan
• Connection for external on/off switch
• LED indication for clip, protect, overtemperature and output level
• Mains operation or 24 V emergency power operation

Specifications:

Power rating	480 W
Power rating at 4 Ω	4 x 120 W
Power rating at 100 V	4 x 120 W
Output impedance	22 V/4 Ω, 50 V/21 Ω, 70 V/41 Ω, 100 V/83 Ω
Channels	4
Inputs	1.2 V, bal.
Frequency range	55-17,000 Hz
S/N ratio	> 90 dBA
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 60 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	133 mm
Depth	370 mm
Rack spaces, RS	3
Weight	25 kg
Connections	4 x XLR (inputs), screw terminals (speakers)

Brand: MONACOR

Type: PA-4120

Quantity: 1

Packing dimensions (W x H x L): 0.48 x 0.22 x 0.54 m

Gross weight: 27.6 kg

Net weight: 25.68 kg

Item weight (w/o accessories): 25 kg