Tender text

PA-900DT

Mono PA mixing amplifier with integrated Dante® module

• 1 x 120 W
• Silent operation due to fanless cooling concept
• 3 balanced mic/line inputs
• Dante® input
• Mic 1 with priority circuit and automatic talkover
• Additional connection for desktop microphone via screw terminal
• 1 aux input
• Speaker outputs via screw terminals
• Line output
• Insert facility, e.g. for effect units, equalizers, feedback controllers
• Input and output level controls
• 2-way tone control for the output
• 20 V phantom power for each microphone input, can be selected individually
• Mains operation or 24 V emergency power operation
• Removable mounting brackets

System requirements Dante®: Windows* 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Specifications:

Peak output power	160 W
Power rating	120 W
Power rating at 4 Ω	120 W
Power rating at 100 V	120 W
Channels	5
Inputs	3 mV (mic), 200 mV (line), 140 mV (aux)
Frequency range	50-15,000 Hz
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 80 dB
THD	< 0.5%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	300 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 9 A
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	88 mm

Depth	275 mm
Rack spaces, RS	2
Weight	9.9 kg
Connections	3 x XLR (mic/line), 1 x RCA L/R (aux), 1 x RJ45 (Dante®), screw terminals (speakers)

Brand: MONACOR

Type: PA-900DT

Quantity: 1

Packing dimensions (W x H x L): 0.37 x 0.16 x 0.52 m

Gross weight: 12.07 kg

Net weight: 10.53 kg

Item weight (w/o accessories): 9.9 kg